




# SIRRA

## CEILING SURFACE



### 1.0 LED

LED 10W | 220-240VAC | 50-60Hz  
COB 3-step | incl. PS | phase-cut dim  
aluminium powder coated  
brushed

0.86kg | IP20 | 0,3-D | A-36°

35°/35° | 355°

|  | CODE     |
|--|----------|
|  | 134164W_ |
|  | 134164E_ |
|  | 134164F_ |
|  | 134164B_ |

### Light Colour Selection

|            | LUMEN   CRI | CODE |
|------------|-------------|------|
| 2700K      | 590   >90   | 3    |
| 3000K      | 640   >90   | 5    |
| 1800-2850K | 440   >90   | 9    |

### 1.0 PAR16

PAR16 max.35W | GU10  
220-240VAC | 50-60Hz  
aluminium powder coated  
brushed

0.74kg | IP20 | 0,9-D

35°/35° | 355°

|  | CODE     |
|--|----------|
|  | 134120W0 |
|  | 134120E0 |
|  | 134120F0 |
|  | 134120B0 |

### OPTIONAL

PAR16 LED GU10 6W  
phase-cut dim

|            | CODE     |
|------------|----------|
| 2700K      | 901228W2 |
| 3000K      | 901228W4 |
| 1800-2850K | 901229S9 |

more lamps and specs on page 471