

STORM MEDIUM SHORT 25 230V

DATA

Collection	STORM SYSTEM®
Product	Storm Medium Short 25 - 230V
Article no.	1A01.0141.xx15

SPECIFICATIONS

Weight	300 g / 900g
Material	Aluminium / Brass
IP protection grade	IP20 / IP44 (with Storm Medium Cabinet)
Labelling	CE
Safety distance	0,3m
Supply	230V max. rating 10W
Insulation class	Class II
Fixture finish	For xx-codes review STORM SYSTEM® - COLOUR CODES ➤

ADDITIONAL REQUIREMENTS


Light Source	MR16 LED (light source not included) review STORM SYSTEM® - CONFIGURATION ➤
	For IES/LDT lux files review STORM SYSTEM® - LUX FILES ➤
	NOTE: when using honey combs the light output will fall with 30% in efficiency

OPTIONAL ACCESSORIES

Black Honeycomb	1AK.0080.02
Silver Honeycomb	1AK.0080.98

INSTALLATION DEPTH




The installation depth may vary depending on the chosen light source and cabinet.
For specific light source conditions - review STORM SYSTEM® - CONFIGURATION ➤



STORM SYSTEM®

The Storm Medium Short 25 is part of the STORM SYSTEM® MEDIUM collection. A collection that includes a wide range of special designed products. The STORM SYSTEM® collection is carefully designed to flush the surface of any ceiling or wall, and all products will appear with an absolute minimum of tolerance and visibility.

Storm Medium Short 25 is designed to rotate 360° and allows a 25° adjustment along the longitudinal axis. It is available in a variation of different colour combinations.



The crossed-out wheeled bin symbol indicates that the item should be disposed of separately from household waste. The item should be handed in for recycling in accordance with local environmental regulations for waste disposal

For more information, please contact info@onea.dk

IMPORTANT INFORMATION

Installation and mounting must be performed by a certified electrician only, and instructions must be followed.

Always make sure the main power is off during installation. Pay attention to the fixture remarks, and always make sure to use the correct voltage.

CLEANING AND MAINTENANCE:


Use a soft moist cloth for cleaning. No further maintenance is required.

WARRANTY:

If the product is defect, please contact your supplier immediately. Please note that warranty will not apply in case of wrongful use or if unskilled personnel attempts to repair.

COMPONENTS

- Storm Medium Short 25
- Retaining ring



PLEASE NOTE:

If the spring on the fixture is damaged, do not proceed installation – contact your dealer!


STORM MEDIUM SHORT 25

ASSEMBLY INSTRUCTION

STEP 1


Connect the cables

Be attentive: Make sure you are using the correct power supply.



STEP 2



Place the bulb in the fixture and mount the retaining ring using light pressure.



STEP 3

Mount the fixture into the plaster ring/
back-mounted ring.
Do this by slightly rotating the fixture
into place.

NOTE: When rotating the fixture
choose the direction with the least
resistance.



IMPORTANT INFORMATION

Disassembly must be performed by a certified electrician only, and instructions must be followed.

WARRANTY:

If the product is defect, please contact your supplier immediately. Please note that warranty will not apply in case of wrongful use or if unskilled personnel attempts to repair.



STORM MEDIUM SHORT 25

DISASSEMBLY INSTRUCTION

STEP 1


Take hold of the fixture and pull down gently, whilst slightly rotating.

NOTE: When rotating the fixture choose the direction with the least resistance.



STEP 2

Remove the retaining ring using light pressure.



STEP 3

Disconnect the cables

