



lix spike solar join Design: Klaus Nolting

für unbefestigte Beet- und Grünflächen for unpaved beds and greens

Lichttechnik:
LED
Lithium-Ionen Akku
1x 2600 mAh
2700K

Betriebsdauer:
automat. Einschaltung bei Dämmerung für die Dauer von etwa 5 Std.

Anschluss:
0,8 m Zuleitung
(05RN8-F 2x0,75 mm²)
inkl. solar join Stecker

ortsveränderlich

Material:
Aluminiumguss
pulverbeschichtet
+ Polycarbonat matt

Schutzart:
IP65

Dieses Produkt enthält eine Lichtquelle der Energieeffizienzklasse E

Lichtrichtung:



light technology:
LED
lithium-ion battery
1x 2600 mAh
2700K

operating time:
automatic switch-on at dusk for a duration of approx. 5 hrs.

connection:
0,8 m supply cable
(05RN8-F 2x0,75 mm²)
incl. solar join plug


movable

material:
aluminium die-casting
powder-coated
+ polycarbonate matt

protection class:
IP65

This product contains a light source of energy efficiency class E

light direction:







Größe in mm
size in mm

Farbe colour	Art.-Nr. item no.	Systemleistung system performance
anthracite RAL 7016	93093-AN-JO	4,4 W/260 lm 1x lix spike solar join - 1,1 W/65 lm 4x lix spike solar join
cool brown	93093-CB-JO	4,4 W/260 lm 1x lix spike solar join - 1,1 W/65 lm 4x lix spike solar join
deep black RAL 9005	93093-BL-JO	4,4 W/260 lm 1x lix spike solar join - 1,1 W/65 lm 4x lix spike solar join





IP44.DE solar join Zubehör accessory

Erforderliches Zubehör required accessory

solar panel L	Solarpanel Lithium-Ionen Akku 4x 2600 mAh 1 m Zuleitung (05RN8-F 2x0,75 mm ²) Schutzart: IP65 solar panel lithium-ion battery 4x 2600 mAh 1 m supply cable (05RN8-F 2x0,75 mm ²) protection class: IP65	Farbe colour	Art.-Nr. item no.
		 anthracite RAL 7016	53110-AN
		 cool brown	53110-CB
		 deep black RAL 9005	53110-BL

Größe in mm
size in mm

Optionales Zubehör optional accessory

	Verlängerungskabel extension cable solar join Stecker auf solar join Buchse Kabel: 05RN8-F 2x0,75 mm ² Schutzart: IP68 solar join plug on solar join socket cable: 05RN8-F 2x0,75 mm ² protection class: IP68		
	2 m		53102
	4 m		53104
	8 m		53108
	Verteiler junction 1x solar join Stecker; 2x/3x/4x solar join Buchse Kabel: 05RN8-F 2x0,75 mm ² Schutzart: IP68 1x solar join plug; 2x/3x/4x solar join socket cable: 05RN8-F 2x0,75 mm ² protection class: IP68		
	port 2		53122
	port 3		53123
	port 4		53124
	T port		53125
	Verschlusskappe Buchse port sealing cap socket port		53121